

Replacement Elements Media

Torit-Tex™ Antistatic	
Product code	9040
Appearance	Black, uncorrugated
Use	Pleatable filter media
Composition	Spun-bond carbon-impregnated polyester with ePTFE membrane
Area weight (DIN 53884)	260 g/m ²
Thickness (DIN 53885)	0.65 mm
Air permeability (DIN 53887)	210-270 m ³ /m ² /h @ 200 Pa
Surface finish	Tetratex® Extreme ePTFE membrane
Surface electrical resistance (DIN 54345)	Less than 10 ⁸ Ω
BIA category (DIN 60335-2-69)	Class M
Continuous temperature (dry heat)*	120°C
Chemical resistance	
Hydrolysis	N/A
Acids	Good
Alkalis	Good
Oxidising agents	Good
Organic solvents	Good
Abrasion resistance	Excellent
Supports combustion	Yes
Application field	Wide pleat spacing and smooth, hydrophobic PTFE membrane provides excellent particle release. Highly recommended for chemical, food and industrial processing when product contamination must be minimised. Excellent performance on moist, hygroscopic or agglomerative dust. Used on applications where electrostatic charges can be dangerous.
	Chemical processing, food processing, general industrial.

*Temperature limitations are for the media only and do not take other filter components into account.

